

Motion Sensor PYR InOut

Characteristics	PYR L12	PYR S12	PYR S5
Power supply	5 - 24Vdc	5 - 24Vdc	5 - 24Vdc
Maximum distance for motion detection	12 mt.	12 mt.	5 mt.
Output with relay contacts	COM/NO/NC	-	-
TTL outputs, positive pulse and negative pulse	-	Y	Y
Input to disable the sensor	Y	Y	Y
Bi-color LED indication	Y	Y	Y
Re-triggerable mode function	on/off (dual mode)	Y	Y
Duration of output pulse with time adjustable	2 sec. to 1 min.	1 sec. to 10 sec.	1 sec. to 10 sec.
Inhibition time adj. between two detections	5 sec. to 12 min.	5 sec. to 12 sec.	5 sec. to 12 sec.
Max. consumption	500mW	70mW	70mW
Stand-by consumption	10mW	20mW	20mW
Dimension mm.	90,4 x 50 x 28,7	70,4 x 50 x 28,7	70,4 x 50 x 22
Case	plastic	plastic	plastic
Available colors	PYR L12/w = white PYR L12/d = dark gray	PYR S12/w = white PYR S12/d = dark gray	PYR S5/w = white PYR S5/d = dark gray

PYR L12/w



PYR S12/w



PYR S5/w

